

Speed dôme analogique extérieur, zoom X36, 650/700TVL


Réf. : VZ-2AF5268-A



Key features

- 1/4" Sony CCD / 1/3" Sony CCD
- 700TVL horizontal resolution
- 36X / 23X optical zoom, 16X digital zoom
- Smart tacking
- True Day/Night, Digital WDR
- 3D intelligent positioning

Dimensions



Camera	
Image Sensor	1/4" Interline Transfer CCD
Effective Pixel	PAL: 976(H)×582(V)
Horizontal Resolution	Color: 700 TVL, B/W: 750 TVL
Min.Illumination	Color: 0.02Lux/(F1.6, AGC ON), 0.0008Lux/(F1.6, AGC ON, IRE × 256) B/W: 0.002Lux/(F1.6, AGC ON), 0.00008Lux/(F1.6, AGC ON, IRE × 256)
White Balance	Auto / Manual / ATW / Indoor / Outdoor
AGC	Auto / Manual
S / N Ratio	≥ 50dB
Shutter Speed	PAL: 1/3 ~1/10,000s, NTSC: 1/4 ~1/10,000s
Digital Noise Reduction	3D DNR
Backlight compensation	BLC
Wide Dynamic Range	Digital WDR
Day & Night	IR Cut Filter
Digital Zoom	16X
Privacy Masking	8 privacy masks programmable, optional multiple colors and mosaics
Focus Model	Auto / Semiautomatic / Manual
Lens	
Focal Length	3.3 ~119mm, 36X
Zoom Speed	Approx 6.0s(Optical Wide-Tele)
Angle of View	57.1~1.7 degree(Wide-Tele)
Min. Working Distance	10 ~1500mm (Wide-Tele)
Aperture	F1.4 ~ F4.2
Pan and Tilt	
Smart tracking	Support
Pan and Tilt Range	Pan: 360° endless; Tilt: -5°~90° (Auto Flip)
Pan and Tilt Speed	Pan Manual Speed: 0.1°~300°/s, Pan Preset Speed: 540°/s Tilt Manual Speed: 0.1°~240°/s, Tilt Preset Speed: 400°/s
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset	255
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the total recording time not less than 10 minutes
Power-off Memory	Support
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
PTZ Position Display	Support
Password Protection	Support
Preset Freezing	Support
Zone Scanning/Display	Scanning within programmed zone, display zone title
Camera Title	Programmable title display
Compass	Support, the north can be set
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan / Day / Night
Alarm	
Alarm Input	2 (7 alarm inputs optional)
Alarm Output	2 relay outputs, alarm response actions configurable
Alarm Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Random scan / Frame scan / Panorama scan / Relay output
Input/ Output	
Video Output	1.0 V[p-p] / 75Ω, PAL / NTSC composite, BNC
General	
RS-485 Protocols	HIKVISION, Pelco-P, Pelco-D, self-adaptive
Power	-A: 24 VAC, max. 40W
Working Temperature	-A: -30°C ~ 65°C(-22°F ~ 149°F);
Humidity	90% or less
Protection Level	IP66 (outdoor dome) TVS 4,000V lightning protection, surge protection and voltage transient protection IK10 (optional)
Dimensions	Φ220×325.5mm (Φ8.66"×12.81")(Outdoor)
Weight	Approx. 5Kg (11.02lbs)



Réf. : VZ-1601ZJ



Réf. : VZ-1601ZJ-CORNER



Réf. : VZ-1601ZJ-POLE



Réf. : VZ-1634ZJ



Réf. : VZ-1662ZJ