

Mini caméra tube extérieure IP 1,3MP 720p/25ims, 1/3" CMOS

Mini caméra tube extérieure IP 3MP 1080p/25ims, 1/3» CMOS


Réf. : VZ-2CD2012-I / VZ-2CD2032-I



Key features

- 1.3MP / 3MP high resolution
- HD real-time video
- 3D DNR & DWDR & BLC
- IR LEDs: up to 30m
- IP66
- PoE
- Compact design
- Bracket included

Dimensions



Camera	VZ-2CD2012-I		VZ-2CD2032-I	
Image sensor	1/3" progressive scan CMOS			
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR		0.07 lux @F1.2, AGC ON, 0 lux with IR	
Shutter time	1/25s (1/30s) ~ 1/100,000s			
Lens	4mm@ F2.0 (6mm, 12mm optional)		4mm@ F2.0 (6mm, 12mm optional)	
	Angle of view: 73.1°(4mm), 46°(6mm), 22°(12mm)		1920 × 1080: Angle of view: 79°(4mm), 49°(6mm), 23.2°(12mm) 2048 × 1536: Angle of view: 70°(4mm), 43.3°(6mm), 20.6°(12mm)	
Lens mount	M12			
Day & night	IR cut filter with auto switch			
Digital noise reduction	3D DNR			
Wide dynamic range	Digital WDR			
Compression Standard				
Video compression	H.264 / MJPEG			
H.264 codec profile	Main profile			
Bit rate	32 Kbps ~ 16 Mbps			
Dual stream	Yes			
Image				
Max. Image Resolution	1280 × 960		2048 × 1536	
Frame rate	50 Hz: 25 fps (1280 × 960), 25 fps (1280 x 720), 25 fps (704 × 576), 25 fps (640 x 480) 60 Hz: 30 fps (1280 × 960), 30 fps (1280 x 720), 30 fps (704 × 576), 30 fps (640 x 480)		50Hz: 20fps (2048 x 1536), 25fps (1920 × 1080), 25fps (1280 x 720) 60Hz: 20fps (2048 x 1536), 30fps (1920 × 1080), 30fps (1280 x 720)	
Image settings	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser			
BLC	Yes, zone configurable			
ROI	Yes, up to 4 configurable areas			
Network				
Network storage	NAS			
Alarm trigger	Motion detection, tampering alarm			
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour			
System compatibility	ONVIF, PSIA, CGI, ISAPI			
General functionalities	User Authentication, watermark, reset button			
Interface				
Communication interface	1 RJ45 10 M / 100 M Ethernet interface			
Reset Button	Yes			
General				
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)			
Power supply	12 VDC ± 10% , PoE (802.3af)			
Power consumption	Max. 5W (max. 7W with ICR on)			
Weather proof rating	IP66			
IR range	Up to 30m			
Dimension	60.4×76.9×139.28 mm (2.4" × 3.0" × 5.5")			
Weight	500g (1.1 lbs)			