

Caméra tube extérieure IP 3MP 1080p/25ims,1/3" CMOS


Réf. : VZ-2CD2632F-I / VZ-2CD2632F-IS



Key features

- 1.3MP / 3MP high resolution
- HD real-time video
- Vari-focal lens
- IR range: up to 30m
- DWDR & 3D DNR & BLC
- IP66
- Onboard storage (up to 64GB)
- (-S) Audio I/O, Alarm I/O

Dimensions



Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.07 lux @F1.2, AGC ON, 0 lux with IR
Shutter time	1/25s (1/30s) ~ 1/100,000s
Lens	2.8 - 12 mm @ F1.4, Angle of view: 105.2°-31.9°
Lens mount	Ø14
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Backlight compensation	Yes, zone configurable
Compression Standard	
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Audio compression	G.711 / G.726 / MP2L2
Audio bit rate	64 Kbps (G.711) / 16 Kbps (G.726) / 32-128 Kbps (MP2L2)
Image	
Max. Image Resolution	2048 × 1536
Frame rate	50Hz: 20fps (2048 × 1536), 25fps (1920 × 1080), 25fps (1280 × 720) 60Hz: 20fps (2048 × 1536), 30fps (1920 × 1080), 30fps (1280 × 720)
Image settings	Rotate mode, Saturation, brightness, contrast, sharpness adjustable through client software or web browser
ROI	Yes, up to 4 configurable areas
Network	
Network storage	NAS
Alarm trigger	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage full, Storage error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI, ISAPI
General functionalities	User authentication, watermark, dual stream
Interface	
Communication interface	1 RJ45 10 M / 100 M Ethernet port
Onboard storage	Built-in Micro SD / SDHC / SDXC card slot, up to 64 GB
General	
Operating conditions	-30 °C ~ 60 °C (-22°F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC ± 10% , PoE (802.3af)
Power consumption	Max. 5.5W (7.5W with ICR on)
Ingress protection level	IP66
IR range	Up to 30m
Dimensions	95×105×258.6 mm (3.74" × 4.13" × 10.18")
Weight	1200g

* -S: 1-ch audio I/O interface, 1-ch alarm I/O interface



Réf. : VZ-1260ZJ



Réf. : VZ-1275ZJ