

Mini dôme extérieur anti-vandale IP 1,3 MP 720p/25ims, 1/3" CMOS


Réf. : VZ-2CD2512F-I



Key features

- Up to 1.3 megapixel (1280 x 960) resolution
- HD real-time video
- IR LEDs (up to 10m)
- Built-in microphone & speaker
- Support on-board storage (up to 64GB)
- IP66

Dimensions



Camera	
Image sensor	1/3" progressive scan CMOS
Min. illumination	0.028 lux@F2.0, AGC on 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm@F2.0, angle of view: 73.1° (4mm) (2.8mm, 6mm optional)
Lens mount	M12
Day & night	-I: ICR
Adjustment angle	Pan: ±30°, tilt: 0~75°, rotation: 0~360°
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Backlight compensation	Yes, zone configurable
Compression standard	
Video compression	H.264 / MJPEG
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Audio compression	G.711 / G.726
Audio bit rate	64 Kbps (G.711) / 16 Kbps (G.726)
Image	
Max. image resolution	1280 x 960
Frame rate	60Hz: 30fps (1280 × 960), 30fps (1280 x 720), 30fps (704 x 576), 30fps (640 x 480)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
Network	
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm, network disconnect, IP address conflict, storage exception, storage error
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour
System compatibility	ONVIF, PSIA, CGI
General functionalities	Flickerless, dual stream, heartbeat, mirror, user authentication, video mask, watermark
Interface	
Communication interface	1 RJ45 10M / 100M ethernet port
On-board storage	Built-in Micro SD/SDHC/SDXC card slot, up to 64 GB
General	
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), humidity 95% or less (non-condensing)
Power supply	DC12V ± 10%, PoE (802.3af)
Power consumption	Max. 5W
Ingress protection level	IP66
Impact protection	IEC60068-2-75Eh, 50J; EN50102, up to IK08
IR range	Up to 10m
Dimensions (mm)	99.9 x 97.5 x 56.5
Weight	350g



Réf. : VZ-1272ZJ-120B



Réf. : VZ-1275ZJ



Réf. : VZ-1276ZJ