

# Moniteur vidéo NEOVO LCD 19"

Réf. : VZ-LCD19-HQ

<b>Panel</b>	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments  Viewing Angle (H/V) Display Colour Response Time	LED-Backlit TFT LCD 19.0" (482 mm) SXGA 1280 x 1024 0.294 mm 250cd/m2 (Typical) 1,000:1 (Typical) Hard Coating (3H), Anti-glare treatment  170°/170° (Typical) 16.7M 3ms (GTG)
<b>Frequency (H/V)</b>		H: 30 kHz - 82 kHz V: 56 Hz - 75 Hz
<b>Input</b>	Analogue Digital	15-Pin D-Sub 24-Pin DVI-D
<b>Audio</b>	Audio In Speaker	1 x Stereo audio in for PC (audio jack, 3.5Ø) 3W x 2
<b>Power</b>	Power Supply Power Requirements Consumption	Internal AC 100 - 240 V, 50 - 60 Hz < 18 W (On) < 0.5 W (Stand-by) < 0.5 W (Off)
<b>Plug &amp; Play</b>	VESA	DCC 2B
<b>Operating Conditions</b>	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
<b>Storage Conditions</b>	Temperature Humidity	-25 °C ~ 55 °C 10% ~ 85%
<b>Mounting</b>	VESA FPMPI	Yes (100 x 100mm)
<b>Tilt</b>	Tilt	-5° ~ +20°
<b>Dimensions</b>	Product (W x H x D) Packaging (W x H x D)	422 x 388 x 195 mm (16.6" x 15.3" x 7.7") 478 x 403 x 140 mm (18.8" x 15.9" x 5.5")
<b>Weight</b>	Product Weight Packaged Product Weight	3.9 kg (8.6 lbs) 5.8 kg (12.8 lbs)
<b>Regulation Approval</b>	Certifications & Compliance	FCC, CB, CE, GOST-R, WEEE, RoHS, REACH
<b>Accessories</b>	Supplied	User manual, 15-Pin D-Sub cable, audio cable, AC power cord



Sleek design with anti-glare display panel for superior viewing comfort



VESA standard wall mount allows for secure mounting



Built-in speakers provide easy access to multimedia applications



Tilt from -5 °C to +20 °C for optimal viewing