Ecran info NEOVO LED 24"

Réf.: VZ-LCD24-INFO

Panel	Panel Type Panel Size Max. Resolution Pixel Pitch Brightness Contrast Ratio Surface Treatments Viewing Angle (H/V) Display Colour Response Time	LED-backlit TFT LCD 24.0" (610 mm) Full HD 1920 x 1080 0.277 mm 250cd/m2 (Typical) 20,000,000:1 (DCR) Hard Coating (3H), Anti-glare treatment 170°/160° (Typical) 16.7M 3ms (GTG)
Frequency (H/V)		H: 30kHz – 83kHz V: 56Hz – 75Hz
Input	Analogue Digital HDMI	15-Pin D-Sub 24-Pin DVI-D HDMI
Audio	Audio In Speaker	3.5mm Audio Line-in 2W x 2
Power	Power Supply Power Requirements Consumption	Internal AC 100 – 240 V, 50-60 Hz < 33W (On) < 0.5W (Stand-by) < 0.5W (Off)
Plug & Play	VESA	DCC 2B
Operating Conditions	Temperature Humidity	0 °C ~ 40 °C 10% ~ 85%
Storage Conditions	Temperature Humidity	-25 °C ~ 55 °C 10% ~ 85%
Mounting	VESA FPMPMI	Yes (100 x 100mm)
Tilt	Tilt	-4° ~ +18°
Dimensions	Product (W x H x D) Packaging (W x H x D)	566 x 395 x 190 mm (22.3" x 15.6" x 7.5") 622 x 423 x 130 mm (24.5" x 16.7" x 5.1")
Weight	Product Weight Packaged Product Weight	4.3 kg (9.5 lbs) 5.7 kg (12.5 lbs)
Regulation Approval	Certifications & Compliance	FCC, CB, CE, BSMI, GOST-R, WEEE, Energy Star, RoHS, REACH
Accessories	Supplied	CD ROM (user manual), 15-Pin D-Sub cable, audio cable, AC power cord



The slim and glossy frame represents a stylish design and also save desktop space



Built-in HDMI input makes the L-W24 easy to be paired with Full HD multimedia advices



VESA standard wall mount allows for secure mounting almost anywhere