

Enregistreur IP

4 flux 720p/25ims ou 2 flux 1080p/25ims avec switch 4 ports POE
8 flux 720p/25ims ou 5 flux 1080p/25ims avec switch 8 ports POE

Réf. : VZ-7604NI-E1/4P/A

Réf. : VZ-7608NI-E2/8P/A




Key features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- 4/8/16-ch network cameras can be connected with 25M/50M/100M incoming bandwidth
- Up to 2 SATA interfaces
- Plug & Play with up to 8 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc

Réf. : VZ-7604NI-E1/4P/A



Réf. : VZ-7608NI-E2/8P/A



1. Power Supply
2. Audio In
3. HDMI Interface
4. LAN Network Interface
5. Audio Out
6. VGA Interface
7. USB Interface
8. Ground
9. Power Switch
10. Network Interfaces with PoE Function
11. Alarm I/O

Video/Audio input	VZ-7604NI-E1/4P/A	VZ-7608NI-E2/8P/A
IP video input	4-ch	8-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)	
Network		
Incoming bandwidth	25Mbps	50Mbps
Outgoing bandwidth	80Mbps	
Remote connection	128	
Video/Audio output		
Recording resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Frame rate	Main stream: 50 fps (P) / 60 fps (N)	
	Sub-stream: 50 fps (P) / 60 fps (N)	
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz	
Audio output	1-ch, RCA (Linear, 1kΩ)	
Decoding		
Live view / Playback resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Capability	4-ch@1080P	8-ch@720P, 6-ch@1080P
Hard disk		
SATA	1 SATA interface for 1 HDD	2 SATA interface for 2 HDDs
Capacity	Up to 4TB for each disk	
External interface		
Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface	
USB interface	1 × USB 2.0 and 1 × USB 3.0	
Alarm in/out	4 / 1	
PoE		
Interface	4 independent 100 Mbps PoE network interfaces	8 independent 100 Mbps PoE network interfaces
Max. Power	50W	120W
Supported standard	AF and AT	
Others		
Power supply	48V DC	220V AC
Consumption(without hard disk)	≤ 10W	
Working temperature	-10 °C ~ +55 °C (+14 °F~ + 131 °F)	
Working humidity	10 % ~ 90 %	
Chassis	1U chassis	19-inch rack-mounted 1U chassis
Dimensions(W × D × H)	315 × 230 × 45mm (12.4 × 9.1 × 1.8 inch)	445 × 290 × 45mm (17.5 × 11.4 × 1.8 inch)
Weight(without hard disk)	≤ 1 Kg (2.2 lb)	