

Enregistreur analogique

4 voies 720p/25ims ou 1080p/12ims et 1 voie IP 1080p

Réf. : VZ-7204HGHI-SH/A

8 voies 720p/25ims ou 1080p/12ims et 2 voies IP 1080p


Réf. : VZ-7208HGHI-SH/A



Key features

- H.264 & Dual-stream video compression
- Support both HD-TVI and analog cameras with adaptive access
- Full channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920x1080P resolution
- Long transmission distance over coax cable
- Support up to 16-ch synchronous playback at 1080P resolution

Rear Panel



- 1 VIDEO IN
- 2 AUDIO IN, RCA Connector
- 3 AUDIO OUT, RCA Connector
- 4 VGA Interface
- 5 HDMI Interface
- 6 USB Port
- 7 LAN Network Interface
- 8 RS-485 Serial Interface
- 9 12VDC Power Input
- 10 Power Switch
- 11 GND
- 12 Alarm I/O

Video/Audio input	VZ-7204HGHI-SH/A	VZ-7208HGHI-SH/A
Video compression	H.264	
Analog and HD-TVI video input	4-ch	8-ch
	BNC interface (1.0Vp-p, 75 Ω)	
Supported camera types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS	
Audio compression	G.711u	
Audio input / Two-way audio in	4-ch, RCA (2.0 Vp-p, 1 KΩ)	
Video/Audio output		
HDMI / VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz	
Encoding resolution	Main stream: 1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA	
Frame rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate	
Video bitrate	32 Kbps-6 Mbps	
Audio output	1-ch, RCA (Linear, 1KΩ)	
Audio bitrate	64 Kbps	
Dual-stream	Support	
Stream type	Video, Video & Audio	
Synchronous playback	4-ch	8-ch
Playback resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF	
Network management		
Remote connections	128	
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS	
Hard disk		
Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface	
SATA	1 SATA interface	
Capacity	Up to 4 TB capacity for each disk	
External interface		
Network interface	1; 10M / 100M self-adaptive Ethernet interface	
Serial interface	1; standard RS-485 serial interface, half-duplex	
USB port	2 × USB2.0	
Alarm in/out	4/1	8/4
General		
Power supply	12V DC	
Consumption (without hard disks)	≤ 15W	≤ 20W
Working temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)	
Working humidity	10% ~ 90%	
Chassis	1U chassis	
Dimensions (W × D × H)	315 × 242 × 45mm (12.4 × 9.5 × 1.8 inch)	
Weight (without hard disks)	≤ 1.5Kg (3.3lb)	