

# Enregistreur analogique

## 16 voies 720P/25ims ou 1080P/12IMS et 2 voies IP 1080P


Réf. : VZ-8116HGHI-SH



### Key features

- H.264 & Dual-stream video compression
- Support both HD-TVI and analog cameras with adaptive access
- Full channel@1080P resolution real-time recording
- HDMI and VGA output at up to 1920x1080P resolution
- Long transmission distance over coax cable
- Support up to 16-ch synchronous playback at 1080P resolution

### Rear Panel



- 1 VIDEO IN
- 2 VIDEO OUT
- 3 AUDIO IN, RCA Connector
- 4 USB Port
- 5 HDMI Interface
- 6 VGA Interface
- 7 CVBS AUDIO OUT and VGA AUDIO OUT
- 8 LAN1 LAN2 Network Interfaces
- 9 RS-485 Serial Interface, Keyboard Interface, ALARM IN and ALARM OUT
- 10 100-240V AC Power Input
- 11 Power Switch
- 12 GND
- 13 LINE IN
- 14 eSATA Interface
- 15 RS-232 Serial Port

Video/Audio input	
Video compression	H.264
Analog and HD-TVI video input	16-ch BNC interface (1.0Vp-p, 75 Ω)
Supported camera types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
Audio compression	G.711u
Audio input	16-ch RCA (2.0 Vp-p, 1 KΩ)
Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Video/Audio output	
HDMI / VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Encoding resolution	Main stream: 1080P / 720P / VGA / 4CIF / CIF Sub-stream: WD1 (non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video bitrate	32 Kbps-10 Mbps
Audio output	2-ch, RCA (Linear, 1KΩ, for VGA output and CVBS output respectively)
Audio bitrate	64 Kbps
Dual-stream	Support
Stream type	Video, Video & Audio
Synchronous playback	16-ch
Playback resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Network management	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Hard disk	
Type	8 SATA interfaces for 8 HDDs; 1 eSATA interface
Capacity	Up to 4 TB capacity for each disk
External interface	
Network interface	2; 10M / 100M / 1000M self-adaptive Ethernet interfaces
Serial interface	RS-232, RS-485, Keyboard
USB port	3 × USB2.0
Alarm in / out	16 / 4
General	
Power supply	100 ~ 240VAC, 47 ~ 63HZ
Consumption (without hard disks)	≤ 65W
Working temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Chassis	19-inch rack-mounted 2U chassis
Dimensions (W × D × H)	445 × 470 × 90 mm (17.5 × 18.5 × 3.5 inch)
Weight (without hard disks)	≤ 8Kg (17.6 lb)