

Enregistreur IP

4 flux 720p/25ims ou 2 flux 1080p/25ims

8 flux 720p/25ims ou 5 flux 1080p/25ims

Réf. : VZ-7604NI-E1/A

Réf. : VZ-7608NI-E2/A



Key features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- HDMI and VGA output at up to 1920x1080P resolution
- 4/8/16-ch network cameras can be connected with 25M/50M/100M incoming bandwidth
- Up to 2 SATA interfaces
- Support network detection, including network delay, packet loss, etc.

Rear Panel

Réf. : VZ-7604NI-E1/A



Réf. : VZ-7608NI-E2/A



1. Power Supply
2. Audio In
3. HDMI Interface
4. LAN Network Interface
5. Audio Out
6. VGA Interface
7. USB Interface
8. Ground
9. Power Switch
10. Alarm I/O

Video/Audio input	VZ-7604NI-E1/A	VZ-7608NI-E2/A
IP video input	4-ch	8-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1KΩ)	
Network		
Incoming bandwidth	25Mbps	50Mbps
Outgoing bandwidth	80Mbps	
Remote connection	128	
Video/Audio output		
Recording resolution	5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Frame rate	Main stream: 50 fps (P) / 60 fps (N)	
	Sub-stream: 50 fps (P) / 60 fps (N)	
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz	
Audio output	1-ch, RCA (Linear, 1kΩ)	
Decoding		
Live view / Playback resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
Capability	4-ch@1080P	8-ch@720P, 6-ch@1080P
Hard disk		
SATA	1 SATA interface for 1 HDD	2 SATA interface for 2 HDDs
Capacity	Up to 4TB for each disk	
External interface		
Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface	
USB interface	1 × USB 2.0 and 1 × USB 3.0	
Alarm in/out	4 / 1	
Others		
Power supply	12V DC	
Consumption(without hard disk)	≤ 10W	
Working temperature	-10 °C ~ +55 °C (+14 °F~ + 131 °F)	
Working humidity	10 % ~ 90 %	
Chassis	1U chassis	380 chassis
Dimensions(W × D × H)	315 × 230 × 45 mm (12.4 × 9.0 × 1.8 inch)	380 × 290 × 48mm (15.0 × 11.4 × 1.9 inch)
Weight(without hard disk)	≤ 1 kg	