

Serveur IP

32 flux 4CIF ou 16 flux 720p/25ims ou 8 flux 1080p/25ims

Réf. : VZ-9532NI-ST



Key features

- Third-party network cameras supported
- Up to 5 Megapixels resolution recording
- Up to 8 SATA interfaces
- HDD quota and group management
- Dual gigabit network interfaces

Rear Panel



1. RS-232 serial interface
2. eSATA interface
3. LAN1, LAN2 network interface
4. RS-485 serial interface, keyboard interface, alarm in and alarm out
5. GND
6. 100 ~ 240VAC power input
7. Power switch
8. USB interface
9. Terminal switch
10. Reset

| Video/Audio input | |
|--|---|
| IP video input | 32-ch |
| Video/Audio output | |
| Recording resolution | 5MP / 3MP / 1080P / UXGA / 720P / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF |
| Hard disk | |
| SATA | 8 SATA interfaces |
| eSATA | 1 eSATA interface |
| Capacity | Up to 4TB capacity for each HDD |
| Disk array (DS-9532NI-RT series supported) | |
| Array type | RAID0, RAID1, RAID5, RAID10 |
| Number of array | 4 |
| Number of virtual disk | 8 |
| External interface | |
| Network interface | 2 RJ-45 10 / 100 / 1000 Mbps self-adaptive Ethernet interfaces |
| Serial interfaces | 1 RS-232 interface (for parameters configuration, maintenance, transparent channel); 1 RS-485 interface; 1 RS-485 keyboard interface (for special keyboard control) |
| USB interface | 3 x USB2.0 |
| Alarm in | 16 |
| Alarm out | 4 |
| General | |
| Power supply | 100 ~ 240 VAC, 6.3A, 50 ~ 60Hz |
| Consumption | ≤ 45 W |
| Working temperature | -10°C ~ +55°C (14 °F ~ 131 °F) |
| Working humidity | 10% ~ 90% |
| Chassis | 19-inch rack-mounted 2U chassis |
| Dimensions (W x D x H) | 445 × 470 × 90 mm (17.52" × 18.5" × 3.54") |
| Weight | ≤ 8 kg (17.64 lb) (without hard disk or DVD-R/W) |